

3 PC. CAST ALUMINUM VENT CAP ASSEMBLY.

CAST ALUMINUM SOLID HINGED ROOF FOR EASY RELAMPING. TOP CONE REFLECTOR CONCEALED UNDER ROOF.

4 CLEAR ACRYLIC (CA) CAGE PANELS SECURE W/CLIPS, SCREWS AND SLOTTED TRACKS OF EXTRUDED CAGE LEGS. OTHER PANELS AVAILABLE, CONTACT FACTORY.

CAST ALUMINUM TOP CAGE FRAME.

18 1/4" SQ.

4 EXTRUDED ALUMINUM CAGE LEGS WELDED TO TOP AND BOTTOM CAGE FRAMES.

PORCELAIN MEDIUM BASE 4KV SOCKET CONCEALED BY MIDDLE CONE REFLECTOR. MOGUL BASE 4KV SOCKET ALSO AVAILABLE. (LAMP NOT SUPPLIED)


CAST ALUMINUM ROUND CONE OPTIC HOLDER ASSEMBLY.

CAST ALUMINUM BOTTOM CAGE FRAME.

BALLAST AND COMPONENT PARTS MOUNTED INSIDE 3 PC. CAST ALUMINUM MOISTURE PROOF BALLAST COMPARTMENT W/HINGED ACCESS DOOR AND SLIDE-OUT BALLAST TRAY. CUSTOMER MUST SPECIFY WATTAGE AND VOLTAGE.

CAST ALUMINUM POST FITTER SLIPS OVER 3" O.D. POST OR TENON AND SECURES WITH FIVE 5/16-18 S.ST'L. SET SCREWS. POST MUST BE ORDERED SEPARATELY.

**OPTIONAL PHOTOCELL
120 VOLT**



E.P.A.: 3.26 (EFFECTED PROJECTED AREA)
 LANTERN IS PREWIRED AND TESTED.
 ELECTRICAL COMPONENTS ARE U.L. LISTED.
 MOUNTING HARDWARE IS SUPPLIED.

Drawing for illustration only - scale approximate

APPROVAL SIGNATURE:		FINISH: _____	<input type="checkbox"/> Mercury Vapor <input type="checkbox"/> Metal Halide <input type="checkbox"/> High Pressure Sodium	 a Philips company <small>350 KING LANE HANOVER PA 17331 PH. (717) 632-4444 - FAX (717) 632-6028</small>	TITLE: "CHARLESTON" 1200 SERIES H.I.D. POST TOP LANTERN		
HEIGHT	43 5/8"	PANELS: _____			WATTAGE: _____	SCALE:	DATE:
WIDTH	18 1/4"	SOCKET: _____	VOLTAGE: _____	1=4	11/13/08	ATV	
PROJECTION	XXXXXX	<input type="checkbox"/> MEDIUM <input type="checkbox"/> MOGUL	POWER FACTOR: <input type="checkbox"/> NPF <input type="checkbox"/> HPF				DWG. NO.
TOP TO OUTLET	XXXXXX						1237C5