



READ THESE INSTRUCTIONS CAREFULLY BEFORE INSTALLING THIS FIXTURE.

This system is intended for installation in accordance with the National Electrical Code (NEC) and local code specifications. Failure to adhere to these codes and instructions may result in serious injury and/or damage to the fixture and will void the warranty. These instructions do not purport to cover all the details or variations in equipment, nor to provide for every possible contingency related to installation, operation, maintenance, or mounting situation. If specific problems occur that are not covered by these instructions, contact your distributor for assistance. Retain these instructions for future reference.

 **SAFETY WARNING:**

ALWAYS TURN OFF/DISCONNECT POWER AND ALLOW TO COOL BEFORE PERFORMING ANY MAINTENANCE, INCLUDING RELAMPING AND CLEANING!

This fixture is rated for a 12W Max. 12V T3-1/4 or T5 Xenon or Incandescent wedge base lamp. Lower wattages may also be used. Included with the fixture is a T3-1/4 10W 12V Xenon wedge base lamp. This fixture can become very HOT! The fixture housing can become hot enough to blister hands. Attention should be paid to where the fixture is mounted, particularly if it can be touched by children or pets. To help prevent premature failure, decreased performance, overheating and risk of fire, keep fixture clean and free of leaves, mulch, debris, and mineral deposits from water. Contact only switch or plug when turning fixture on or off. Do NOT touch hot housing. Turn off or unplug fixture and allow to cool before relamping. Keep lamp away from combustibles. Do NOT touch lamp with bare hands at any time. Use a soft cloth since oil from skin may damage lamp. The fixture can be cleaned using a soft cloth and a solution of mild liquid soap and warm water. Wipe clean and dry with a soft, lint-free dry cloth. Avoid polishing fixture.

FOR USE ONLY WITH LOW VOLTAGE LANDSCAPE LIGHTING POWER UNITS THAT ARE RATED MAXIMUM 25 AMPS, 15 VOLTS PER CIRCUIT.

Do not install fixture within 10 feet (1.52 meters) of a pool, spa or fountain.

INSTALLATION INSTRUCTIONS

1. Make sure power is turned OFF before installing or servicing this fixture.
2. Drill pilot holes for #8 screws (1-3/4" apart) using above full size figure as a template.
3. Screw #8 screws in to pilot holes leaving approximately 3/16" to 1/4" gap between the head of the screw and the mounting surface. (Note: Screws 1/2" to 5/8" in length are recommended.)
4. Place head of top screw through keyhole of top slot, put fixture against mounting surface and slide fixture down over threads of both screws to hang it.
5. Tighten bottom screw to secure fixture to the mounting surface.
6. Wire fixture following instructions below for low voltage connector.
7. Turn power ON.