



**READ THESE INSTRUCTIONS CAREFULLY BEFORE INSTALLING THIS FIXTURE.**

This system is intended for installation in accordance with the National Electrical Code (NEC) and local code specifications. Failure to adhere to these codes and instructions may result in serious injury and/or damage to the fixture and will void the warranty. These instructions do not purport to cover all the details or variations in equipment nor to provide for every possible contingency related to installation, operation, maintenance, or mounting situation. If special problems occur that are not covered by these instructions, contact your distributor for assistance. Retain these instructions for future reference.

GFI protection fixtures which may come in contact with or be exposed to moisture (i.e. outdoors) shall be installed on a GFI (Ground Fault Interruptor) protected circuit.

**INSTALLATION IN PLASTER WALLS**

1. Remove lamp from fixture. The shock from installation may cause the lamp to fail prematurely.
2. Mark the location of the box on the wall material.
3. Cut hole in wall material to slip in fixture junction box. Remove wall material.
4. Remove insulation which would come within six (6) inches of the fixture junction box.
5. Insert fixture junction box into cut hole. Draw screws tight on both sides of the fixture until the junction box is clamped tightly against the wall material.
6. Install lamp in fixture. Install screws through cover plate and into junction box.

**INSTALLATION IN MASONRY OR CONCRETE WALLS**

1. Remove clamps from fixture junction box.
2. Secure junction box using good masonry procedures.
3. Install screws through cover plate and into junction box.

**INSTALLATION TO REPLACE EXISTING FIXTURE**

1. Mark the location of the box on the wall material.
2. Remove insulation which would come within six (6) inches of the fixture junction box.
3. Insert fixture junction box into pre-existing hole. Draw screws tight on both sides of the fixture until the junction box is clamped tightly against the wall material.
4. Install lamp in fixture. Install screws through cover plate and into junction box.