



**READ THESE INSTRUCTIONS CAREFULLY BEFORE INSTALLING THIS FIXTURE.**

This system is intended for installation in accordance with the National Electrical Code (NEC) and local code specifications. Failure to adhere to these codes and instructions may result in serious injury and/or damage to the fixture and will void the warranty. These instructions do not purport to cover all the details or variations in equipment, nor to provide for every possible contingency related to installation, operation, maintenance, or mounting situation. If specific problems occur that are not covered by these instructions, contact your distributor for assistance. Retain these instructions for future reference.

**⚠ SAFETY WARNING:**

**ALWAYS TURN OFF/DISCONNECT POWER AND ALLOW TO COOL BEFORE PERFORMING ANY MAINTENANCE, INCLUDING RELAMPING AND CLEANING!**

This fixture can become very HOT! The fixture housing and lens, especially if it is glass, can become hot enough to blister hands. The housing should not be installed in insulating materials such as bark, vermiculite, etc. for the full depth of the housing. Surface use of these materials around BUT NOT ON TOP of the fixture is acceptable. Attention should be paid to where the fixture is mounted, particularly if it can be touched by children or pets. To help prevent premature failure, decreased performance, overheating and risk of fire, keep fixture and lens clean and free of leaves, mulch, debris, and mineral deposits from water. Do not operate fixture with a missing or damaged lens/lens assembly. Contact only switch or plug when turning fixture on or off. Do NOT touch hot lens or housing. Turn off or unplug fixture and allow to cool before relamping. Keep lamp away from combustibles. Do NOT touch lamp with bare hands at any time. Use a soft cloth since oil from skin may damage lamp. The fixture and lens can be cleaned using a soft cloth and a solution of mild liquid soap and warm water. Wipe clean and dry with a soft, lint-free dry cloth. Avoid polishing fixture or lens. For use only with low voltage landscape lighting power units that are rated maximum 25 amps, 15 volts per circuit. Do not install fixture within 10 feet (1.52 meters) of a pool, spa or fountain.

**INSTALLATION INSTRUCTIONS**

1. Thread fixture onto ground mounted stake or box (not supplied).
2. Loosen shroud screw (see illustration above) and remove shroud.
3. Insert MR16 lamp (50 W MAX.) (not supplied) into socket.
4. Replace shroud, rotate to desired position, and tighten screw.
5. Loosen screw in arm, aim fixture to desired position, and tighten screw.
6. Wire fixture following the directions for the low voltage connector on the back of this page or hardwire to low voltage cable.

**HEAT SHIELD INSTRUCTIONS**

Depending on how the fixture is mounted you may need to adjust the placement of the heat shield. The heat shield should always be on top of the lamp assembly. Failure to adjust the heat shield properly may cause the outside of the fixture to become excessively hot and be a safety hazard for the customer to touch.

